# LGMG SRIGZED

**DIESEL RT SCISSOR LIFT** 




# **LGMG Diesel RT Scissor Lift**


## **SPECIFICATIONS**

Measurements         Metric         Imperial           Work Height Max.         17.9m         58'9"           Image: Platform Height - Raised         15.9m         52'2"           Platform Height - Stowed         2.08m         6'10"           Platform Length         3.98/4.81m         13'1"/15'9"           Platform Width         1.83m         6'           Overall Length (with ladder)         4.9m         16'1"           Overall Width         2.3m         7'7"           Overall Height - Rails down         2.5m         8'2"           Overall Height - Rails down         2.5m         8'2"           Overall Height - Rails down         2.5m         8'2"           Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY         Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.35m </th <th>MODELS</th> <th>SR1623D (</th> <th>SR5390D)</th>	MODELS	SR1623D (	SR5390D)
♣ Platform Height - Raised         15.9m         52'2"           ♠ Platform Height - Stowed         2.08m         6'10"           ♠ Platform Length         3.98/4.81m         13'1"/15'9"           ♠ Platform Width         1.83m         6'           ♠ Overall Length (with ladder)         4.9m         16'1"           ♠ Overall Width         2.3m         7'7"           ♠ Overall Height - Rails up         3.18m         10'5"           Overall Height - Rails down         2.5m         8'2"           ♠ Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ♠ Wheelbase         2.85m         9'4"           ♠ Over Courter         4./ 4         4           ₱ Platform Capacity         680kg         1,500 lbs           ₱ Platform Capacity         5.33m         17'6"           ₱ R	Measurements	Metric	Imperial
● Platform Height - Stowed         2.08m         6'10"           ● Platform Length         3.98/4.81m         13'1"/15'9"           ● Platform Width         1.83m         6'           ● Overall Length (with ladder)         4.9m         16'1"           ● Overall Width         2.3m         7'7"           ● Overall Height - Rails up         3.18m         10'5"           Overall Height - Rails down         2.5m         8'2"           ● Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ● Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Size         835x290mm         33"x11"	Work Height Max.	17.9m	58'9''
● Platform Length         3.98/4.81m         13'1"/15'9"           ● Platform Width         1.83m         6'           ● Overall Length (with ladder)         4.9m         16'1"           ● Overall Width         2.3m         7'7"           ● Overall Height - Rails up         3.18m         10'5"           Overall Height - Rails down         2.5m         8'2"           ● Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ● Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres	Platform Height - Raised	15.9m	52'2"
● Platform Width         1.83m         6'           ● Overall Length (with ladder)         4.9m         16'1"           ● Overall Width         2.3m         7'7"           ● Overall Height - Rails up         3.18m         10'5"           Overall Height - Rails down         2.5m         8'2"           ● Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ● Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER	Platform Height - Stowed	2.08m	6'10''
③ Overall Length (with ladder) ③ Overall Width ② Overall Width ② Overall Height - Rails up ③ Overall Height - Rails down ② S.5m ③ Extension Deck (Front / Rear) ③ Wheelbase ③ C.85m ④ '' ③ Wheelbase ④ C.85m ④ '' ⑤ Overall Height - Rails down ② S.5m ⑤ S'2" ⑤ Extension Deck (Front / Rear) ⑤ Wheelbase ② C.85m ⑤ '' ⑥ Wheelbase ④ C.85m ⑤ '' ⑥ '' Ø Wheelbase ⑤ C.23m ⑤ '' Ø '' PRODUCTIVITY  Max. Platform Occupancy (in/out) ④ 4 / 4  Platform Capacity ⑤ 680kg ⑤ 1,500 lbs Platform Capacity ⑤ 680kg ⑤ 1,500 lbs Platform Capacity ⑤ 680kg ⑤ 1,500 lbs Platform Capacity ⑤ 53kg ⑥ 510 lbs Drive Height ⑥ 3.5m ⑥ 27'11" ⑥ Gradeability - Stowed ⑥ 40%  Min. Turning Radius ⑥ 5.35m ⑥ 17'6"  Raise/Lower Speed ⑥ 55 / 55s  Brakes ⑥ Four-wheel brake  Drive Mode ⑥ 4x4 ⑥ Tires Type ⑥ Solid ⑥ Tires Size ⑥ 835x290mm ⑥ 33"x11" ⑥ Ground Pressure, Tyres ⑥ 888.31 kPa ⑥ 128.8 psi  POWER  Power Source ⑥ Kubota 36kw/48.3hp □ Deutz 36.4kw/48.8hp □ Fuel Tank Capacity ⑥ 100L ⑥ 26.4gal  HYDRAULIC SYSTEM  Hydraulic Oil Volume  140L ⑥ 37gal  WEIGHT  Machine Weight (7.4m platform)  8,200kg ⑥ 18,080 lbs	Platform Length	3.98/4.81m	13'1''/15'9''
● Overall Width         2.3m         7'7"           ● Overall Height - Rails up         3.18m         10'5"           Overall Height - Rails down         2.5m         8'2"           ● Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ● Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L	Platform Width	1.83m	6'
⑤ Overall Height - Rails up         3.18m         10'5"           Overall Height - Rails down         2.5m         8'2"           ⑤ Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ⑥ Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp           Deutz 36.4kw/48.8hp         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume <td>Overall Length (with ladder)</td> <td>4.9m</td> <td>16'1"</td>	Overall Length (with ladder)	4.9m	16'1"
Overall Height - Rails down         2.5m         8'2"           ● Extension Deck (Front / Rear)         1.45/1.14m         4'9"/3'9"           ● Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27"11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp         Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM         140L         37gal           WEIGHT         Machine Weight (7.4m platform)         8,200kg         18,080 lbs </td <td>Overall Width</td> <td>2.3m</td> <td>7'7"</td>	Overall Width	2.3m	7'7"
■ Extension Deck (Front / Rear)  ■ Wheelbase  Ground Clearance-Center  PRODUCTIVITY  Max. Platform Occupancy (in/out)  Platform Capacity  Platform Capacity - Extension  Drive Height  Gradeability - Stowed  Min. Turning Radius  Raise/Lower Speed  Drive Mode  Tires Type  Ground Pressure, Tyres  POWER  Power Source  Kubota 36kw/48.3hp  Fuel Tank Capacity  Fuel Tank Capacity  Machine Weight (7.4m platform)  1.45/1.14m  4'9"/3'9"  2.85m  9'4"  4''  680kg  1,500 lbs  1,500 lbs  510 lbs  27'11"  88.5m  27'11"  680kg  1,500 lbs  1,500 lbs  1,500 lbs  510 lbs  55 / 55s  Four-wheel brake  Four-wheel brake  55 / 55s  Four-wheel brake  128.8 psi  POWER  Kubota 36kw/48.3hp  Deutz 36.4kw/48.8hp  Fuel Tank Capacity  100L  37ggl  WEIGHT  Machine Weight (7.4m platform)  8,200kg  18,080 lbs	Overall Height - Rails up	3.18m	10'5"
● Wheelbase         2.85m         9'4"           Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27"11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Overall Height - Rails down	2.5m	8'2"
Ground Clearance-Center         0.23m         9"           PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp         128.8 psi         Poutz 36.4kw/48.8hp         Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM         140L         37gal         WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Extension Deck (Front / Rear)	1.45/1.14m	4'9"/3'9"
PRODUCTIVITY           Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp         Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM         Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Wheelbase	2.85m	9'4"
Max. Platform Occupancy (in/out)         4 / 4           Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp         Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM         Hydraulic Oil Volume         140L         37gal           WEIGHT         Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Ground Clearance-Center	0.23m	9''
Platform Capacity         680kg         1,500 lbs           Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp           Power Source         Kubota 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	PRODUCTIVITY		
Platform Capacity - Extension         230kg         510 lbs           Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp         Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM         Hydraulic Oil Volume         140L         37gal           WEIGHT         Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Max. Platform Occupancy (in/out)	4 / 4	
Drive Height         8.5m         27'11"           Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp           Deutz 36.4kw/48.8hp         Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Platform Capacity	680kg	1,500 lbs
Gradeability - Stowed         40%           Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Platform Capacity - Extension	230kg	510 lbs
Min. Turning Radius         5.33m         17'6"           Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Drive Height	8.5m	27'11"
Raise/Lower Speed         55 / 55s           Brakes         Four-wheel brake           Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Gradeability - Stowed	40%	
Brakes Four-wheel brake  Drive Mode 4x4  Tires Type Solid  Tires Size 835x290mm 33"x11"  Ground Pressure, Tyres 888.31 kPa 128.8 psi  POWER  Power Source Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp Fuel Tank Capacity 100L 26.4gal  HYDRAULIC SYSTEM  Hydraulic Oil Volume 140L 37gal  WEIGHT  Machine Weight (7.4m platform) 8,200kg 18,080 lbs	Min. Turning Radius	5.33m	17'6''
Drive Mode         4x4           Tires Type         Solid           Tires Size         835x290mm         33"x11"           Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER           Power Source         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Raise/Lower Speed	55 / 55s	
Tires Type Solid  Tires Size 835x290mm 33"x11"  Ground Pressure, Tyres 888.31 kPa 128.8 psi  POWER  Power Source Kubota 36kw/48.3hp	Brakes	Four-wheel brake	
Tires Size 835x290mm 33"x11"  Ground Pressure, Tyres 888.31 kPa 128.8 psi  POWER  Power Source Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp Fuel Tank Capacity 100L 26.4gal  HYDRAULIC SYSTEM  Hydraulic Oil Volume 140L 37gal  WEIGHT  Machine Weight (7.4m platform) 8,200kg 18,080 lbs	Drive Mode	4x4	
Ground Pressure, Tyres         888.31 kPa         128.8 psi           POWER         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Tires Type	So	lid
POWER  Power Source  Fuel Tank Capacity  HYDRAULIC SYSTEM  Hydraulic Oil Volume  140L  37gal  WEIGHT  Machine Weight (7.4m platform)  8,200kg  18,080 lbs	Tires Size	835x290mm	33"x11"
Power Source         Kubota 36kw/48.3hp Deutz 36.4kw/48.8hp           Fuel Tank Capacity         100L         26.4gal           HYDRAULIC SYSTEM           Hydraulic Oil Volume         140L         37gal           WEIGHT           Machine Weight (7.4m platform)         8,200kg         18,080 lbs	Ground Pressure, Tyres	888.31 kPa	128.8 psi
Fower Source  Deutz 36.4kw/48.8hp Fuel Tank Capacity  HYDRAULIC SYSTEM  Hydraulic Oil Volume  140L  37gal  WEIGHT  Machine Weight (7.4m platform)  8,200kg  18,080 lbs	POWER		
Fuel Tank Capacity 100L 26.4gal  HYDRAULIC SYSTEM  Hydraulic Oil Volume 140L 37gal  WEIGHT  Machine Weight (7.4m platform) 8,200kg 18,080 lbs	Power Source		
Hydraulic Oil Volume 140L 37gal  WEIGHT  Machine Weight (7.4m platform) 8,200kg 18,080 lbs	Fuel Tank Capacity		
WEIGHT  Machine Weight (7.4m platform) 8,200kg 18,080 lbs	HYDRAULIC SYSTEM		
Machine Weight (7.4m platform) 8,200kg 18,080 lbs	Hydraulic Oil Volume	140L	37gal
	WEIGHT		
	Machine Weight (7.4m platform)	8,200kg	18,080 lbs
		8,100kg	17,860 lbs

STANDARD FEATURES	5	
Proportional control	Tilt alarm with lift cut-out	
Foldable guardrail	Overload sensing system	
Emergency stop device	Descent alarm with flashing beacon	
Manual brake release	All motions alarm	
Emergency descent	Intelligent diagnostic system	
Oscillating axle	Auto-leveling outriggers	
Self-lock entry gate	Solid tires	
AC power to platform		

OPTIONAL	
Telematics	Solid non-marking tires
Pipe racks	Foam-filled tires
Cold weather package	Foam-filled non-marking tires
Biodegradable hydraulic oil	





Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

## LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283

#### LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands Email: sales@lgmgeurope.com Tel: +31 850 642 777

#### LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States Email: sales@lgmgna.com Tel: +1 833 288 5464



