



Self-propelled **Electric Articulating Boom Lift**

The Articulating Boom Lift provides multi-directional positioning (raising, lowering and moving side-to-side) and is ideal for accessing hard-to-reach workspaces.

Partner of



ElectroMech

| Solutions | Service | Satisfaction |

Self-propelled Electric Articulating Boom Lift

Partner of



Technical Parameter

Model	Unit	GTZZ14EJ	GTZZ16EJ
Specification			
Max.Platform Height	m	14	15.7
Max.Working Height	m	16	17.7
Max.Horizontal Reach	m	7.6	9.3
Max.up and over clearanse	m	7.8	7.8
Turning Radius-Outside	m	3.51	3.31
Turning Radius-Inside	m	1.15	0.7
Turntable Tail swing	mm	0	50
Turntable Rotation	°	365	365
Platform Rotation	°	160	160
Fly Jib Rotation	°	142	142
Gradeability	%	30	30
Lift Capacity	kg	230	230
Drive Speed-Stowed	km/h	0 ~ 5.2	0 ~ 5.2
Drive Speed-Raised	km/h	0 ~ 0.8	0 ~ 0.8
Allowable Wind Speed	m/s	12.5	12.5
Allowable Working Slope	°	5	5
Allowable Lateral Force	N	400	400
Dimensions			
Overall Length-Stowed	m	6	6.8
Overall Width-Stowed	m	1.73	1.9
Overall Height-Stowed	m	2	2
Ground Clearance	m	0.22	0.22
Wheel Base	m	1.9	1.9
Platform Dimensions	m	1.45x0.85x1.1	1.45x0.85x1.1
Total Weight	kg	7100	7300kg
Tires Type		250x15 / solid	250x15 / solid
Control Voltage	V	12	12
Battery	V/Ah	8x6V/420Ah	8x6V/420Ah

Due to technical updates, product configuration and parameters are subject to change without prior notice. This manual is for reference only, and the company reserves the right of interpretation.



ElectroMech

| Solutions | Service | Satisfaction |

Corporate Office & Plant

**ElectroMech Material Handling
Systems (India) Pvt. Ltd.**

Gat No. 316, At post Kasar Amboli,
Tal. Mulshi, Dist. Pune 412 111 INDIA

Telefax : +91-20-6654 2222
E-mail : sinoboom@emech.in

Contact



www.emech.com

© Copyright 2019 | All names, logos and monograms used in this brochure are registered trademarks of respective companies.

follow us on:

Technical changes reserved